

COMPANY:
CONTACT:
EMAIL or FAX:

DATE:\_

## **STAINLESS STEEL TANK WORKSHEET**

Standard Features for Tanks:  • 304 stainless steel  • Standard –or- Deluxe Finish  • Open top with flanged lip		Qty:	Standard Features for Covers:  • 304 stainless steel, 14 gauge  • Standard –or- Deluxe Finish  • Loose-fitting, 1/3 – 2/3 hinge		Qty:
	Bottoms: 15° cone, slope or dish One drain fitting up to 4", with 12"		Handle		
	floor				
•	Legs are stainless steel				
1. Model n	10.:	and/or- <b>Containe</b>	er size: (working gallons	s)	
2. Finish:	•Standard =		& out. Interior welds gro		velds wire brushed.
	• Deluxe =	•	passivated & leak tested		liched Exterior
	•	• , ,	nside & out. Interior weld nitary bead. All welds pla		
			cation Packet Required		mpliance Statement
	hat will be in the tank,	Widterfal certiff	eation racket negative	Standard Cover	·
specific gra	avity, weight per gallon:			<sup>1</sup> / <sub>3</sub> - <sup>2</sup> / <sub>3</sub> hinge	
Specific di	mensions of tank, if other th	nan catalog:			
•	nside diameter:	•		i	
	traight side height:			 	
	learance to the floor:		/ n		U /
3. Bottom	type: (circle one) • 15°	Cone • Sloped • D	Dished \ ~	1 1	
				1	
	ottom drain is required?				
• Drain size		4" other	clamp mount		
	e: FNPT ½ Coupler	<del></del>	mixer bracket		
•	e) 150# ANSI Flange	Iri-Clamp Flan	ge ▼	<u> </u>	- channels/beams
• Other:			<u> </u>		
			<b>A</b>   <b>C</b>	<b>↑</b>	
5. Popular	Optional Items:			<u> </u>	
• 0	Clamp mount mixer bracket:				
• E	quipment bridge: (channels	s/beams)			
• E	Baffles:				
	Sight glass:		over all	 inside	straight
• L	iquid level gauge: .		height	diameter	side
• 3	16 stainless steel, in lieu of	304s.s.		<u> </u>	
	ressurized Tank (ASME Code Max Temp: Max	•			
• J;	ackets: (Heating/Cooling) Non-ASME Code (N	Jo Pressure)			
	ASME Code (Certifi	ed & Stamped)	\		
• 0	Max Temp: asters:	Max Pressure:			
	orklift Channels on tank sides	: 📙		<b>T</b>	<u></u>
6. Special	Cover Requirements:				
-	flixer slot, 1½" x 6" .				1
	Other:				
					<u> </u>