



**SPECIFICATIONS:**  
 MOTOR: 3/4HP GEAR-DRIVE MOTOR, 175RPM.  
 SEAL: EXTERNALLY-MOUNTED DRY-RUNNING.  
 IMPELLER:  $\phi$  21" 3-BLADE HYDROFOIL.  
 MOUNT: 3" TRICLAMP. OTHER SIZES/TYPES  
 AVAILABLE UPON REQUEST.  
 MATERIALS: 316SS WETTED PARTS

$\phi$  21" 3-BLADE  
 HYDROFOIL, 316SS

<p><b>PROPRIETARY AND CONFIDENTIAL</b>          THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INDCO INCORPORATED. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDCO INCORPORATED IS PROHIBITED.</p>			DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm$ ANGULAR: MACH $\pm$ BEND $\pm$ TWO PLACE DECIMAL $\pm$ THREE PLACE DECIMAL $\pm$	NAME	DATE	<p><b>PhG-075T MIXER          GENERAL ARRANGEMENT</b></p>	
			MATERIAL	DRAWN	MH		9/20/11
			FINISH	CHECKED			
	NEXT ASSY	USED ON		ENG APPR.			
	APPLICATION	DO NOT SCALE DRAWING		MFG APPR.			
				Q.A.			
				COMMENTS:			
				SCALE: 1:8	WEIGHT:		
				SIZE <b>A</b>	DWG. NO. 31Q1035 - PhG-075T	REV. 0	
						SHEET 1 OF 1	